

Kod Towaru	MODEL	Wydajność m3/h	WYDAJNOŚĆ CHŁODNICZA DLA R404A PRZY TEMP.PAR./TEMP.SKR.				Przyłącza ssanie/tłoczenie	Wymiary WxDxH (mm) (szer./gł./wys.)	CENA EUR
			+5°C/+40°C	-5°C/+40°C	-15°C/+40°C	-25°C/+40°C			sprężarka
001968	DLE-20X-EW L	9,9	9450W	6400W	4050W	2350W	7/8" x5/8"	330x470x385	1 389
016029	DLJ-30X-EW L	14,5	14150W	9750W	6400W	3900W	7/8" x5/8"	330x470x385	1 858
001961	DLL-40X-EW L	18,2	18400W	12550W	8150W	4950W	1 1/8" x5/8"	330x470x385	2 038
015843	DLSG-40X-EW L	22,5				6350W	1 1/8" x5/8"	330x470x385	2 038
001964	D2SA-45X-EW L	22,4		14750W	9900W	6200W	1 1/8" x7/8"	330x560x395	2 078
001969	D2SA-55X-EW L	22,4		15000W	9800W	5950W	1 1/8" x7/8"	330x560x395	2 448
001967	D2SC-55X-EW L	26,8		17900W	11900W	7350W	1 1/8" x7/8"	330x560x395	2 805
001962	D2SC-65X-EW L	26,8	25600W	17800W	11800W	7350W	1 1/8" x7/8"	330x560x395	2 912
015837	D2SK-65X-EW L	31,2		21400W	14150W	8800W	1 1/8" x7/8"	330x560x395	2 947
015838	D3SA-75X-AW M	32,2	31500W	21500W	14050W	8500W	1 3/8" x1 1/8"	370x655x480	3 723
025363	D3SC-75X-AW M	38,0		22900W	15400W	9850W	1 3/8" x1 1/8"	370x655x480	3 765
015839	D3SC-100X-AW M	38,0	37500W	25700W	16800W	10350W	1 3/8" x1 1/8"	370x655x480	3 901
015840	D3SS-100X-AW M	49,9		32500W	21900W	13950W	1 3/8" x1 1/8"	370x680x480	4 674
014275	D3SS-150X-AW M	49,9	49000W	34500W	23100W	14650W	1 3/8" x1 5/8"	370x680x480	4 686
025364	D4SF-100X-AW M	56,0		38000W	25200W	15900W	1 5/8" x --	485x680x495	5 215
025365	D4SA-200X-AW M	56,0	55000W	38000W	25200W	15600W	1 5/8" x1 1/8"	485x650x495	5 900
025366	D4SL-150X-AW M	70,8		48000W	32000W	20600W	1 5/8" x --	490x680x495	5 747
025367	D4SH-250X-AW M	70,8	67500W	46500W	31000W	19200W	2 1/8" x1 1/8"	490x670x495	6 829
001971	D4ST-200X-AW M	84,7		57500W	38500W	24500W	2 1/8" x --	490x725x495	6 538
015315	D6SA-300X-AW M	84,0	80500W	55500W	36500W	22400W	2 1/8" x --	540x740x490	8 386
025368	D6SL-250X-AW M	106,0		69500W	47500W	30500W	2 1/8" x --	540x740x490	7 806
025369	D6ST-320X-AW M	127,0		82000W	55500W	35500W	2 1/8" x --	540x740x545	8 987