



SOLD FRUIT (rozstaw lamel 7 mm)

Symbol	Model	Wydajność SC2 (R 404A) $t_p=0^{\circ}\text{C} / \Delta T 8\text{K}$	Wydajność (R 404A) $t_p=0^{\circ}\text{C} / \Delta T 5\text{K}$	Powierzchnia lameli [m ²]	Wentylatory szt x średn.	Przepływ powietrza m ³ /h	Cena z grzałkami Netto / Euro	Cena bez grzałek Netto / Euro
		kW	kW		szt. x mm			
022556	FC.N.35.3.08-4M	9,20	6,90	59	3 X 350	6510	1540	1326
022558	FC.N.35.4.08-4M	12,20	9,15	78	4 X 350	8680	1842	1580
022559	FC.N.35.5.08-4M	15,50	11,63	97	5 X 350	10850	2275	1931
022561	FC.N.45.2.08-4T	13,50	10,13	78	2 X 450	10200	2231	1916
022563	FC.N.45.3.08-4T	19,70	14,78	116	3 X 450	14400	2870	2485
022565	FC.N.45.4.08-4T	26,30	19,73	151	4 X 450	19200	3618	3059
022551	FC.N.45.5.08-4T	32,80	24,60	188	5 X 450	24000	4289	3649

SYMBOL	Model	LICZBA WENTYLATORÓW	WYMIARY (mm)									PRZYŁĄCZA		ODPŁYW SKROPLIN
			A	B	C	C'	D	E	F	H	I	IN	OUT	
022556	FC.N.35.3.08-4M	3	1800	130	1520	/	130	450	500	540	570	5/8"	28	1"
022558	FC.N.35.4.08-4M	4	2300	130	2020	1000	130	450	500	540	570	5/8"	28	1 1/4"
022559	FC.N.35.5.08-4M	5	2800	130	2520	1000	130	450	500	540	570	5/8"	28	1 1/4"
022561	FC.N.45.2.08-4T	2	1800	155	1480	/	155	600	550	740	660	16	28	1 1/4"
022563	FC.N.45.3.08-4T	3	2525	155	2205	1450	155	600	550	740	660	22	35	1 1/4"
022565	FC.N.45.4.08-4T	4	3250	155	2930	1450	155	600	550	740	660	28	42	1 1/4"
022551	FC.N.45.5.08-4T	5	3975	155	3655	1450	155	600	550	740	660	35	54	2"

SYMBOL	Model	WYRZUT POWIETRZA	OBJĘTOŚĆ WEŻOWNICY	MOC GRZAŁEK	OBROTY WENTYLATORÓW	POZIOM HAŁASU	MOC WENTYLATORÓW	POBÓR PRĄDU WENTYLATORÓW	WAGA
		m	dm ³	kW	RPM	dB(A) - 5m	W	A	
022556	FC.N.35.3.08-4M	15	9	4,5	1450	55	540	2,1	64
022558	FC.N.35.4.08-4M	15	12	6	1450	56	720	2,8	85
022559	FC.N.35.5.08-4M	15	15	7,6	1450	57	900	3,5	100
022561	FC.N.45.2.08-4T	25	12	6,6	1400	53	1180	1,8	97
022563	FC.N.45.3.08-4T	25	18	9,6	1400	55	1770	2,7	132
022565	FC.N.45.4.08-4T	25	24	12,6	1400	56	2360	3,6	172
022551	FC.N.45.5.08-4T	25	30	15,6	1400	57	2950	4,5	210