

Skraplacze powietrzne LU-VE - pionowe- wybrane modele



SYMBOL TOWARU	MODEL	Wydajność dt=15K, R404A [kW]	Poziom hałasu dB [A]	Średnica wentylatora [mm]	Wymiary vertical		Podłączenie		CENA NETTO EUR
					szer/gł/wys [mm]	[mm]	[mm]		
							wlot	wylot	
SHVN 350 4P V	7/7	8,0	40	1 x 350	723/363/573		16	16	414
	9/4	9,1	40	1 x 350	723/363/573		16	16	470
	10/2	9,8	40	1 x 350	723/363/573		18	18	526
	15/5	16,0	43	2 x 350	1294/363/573		18	18	751
	19/0	18,2	43	2 x 350	1294/363/573		22	22	847
	20/4	19,6	43	2 x 350	1294/363/573		22	22	940
	23/2	24,0	45	3 x 350	1853/363/573		22	22	1 075
	28/5	27,3	45	3 x 350	1853/363/573		22	22	1 231
	30/6	29,4	45	3 x 350	1853/363/573		28	28	1 393
	38/0	36,4	46	4 x 350	2408/363/573		28	28	1 653
SHVN 500 4P V	50	50,4	53	2 x 500	1895/470/830		35	28	2 326
	58	54,2	53	2 x 500	1895/470/830		35	28	2 606
	73	75,6	54	3 x 500	2705/470/830		35	28	3 359
	83	81,3	54	3 x 500	2705/470/830		42	35	3 748
	98	100,8	56	4 x 500	1895/470/1645		42	35	4 649
	110	108,4	56	4 x 500	1895/470/1645		54	42	5 196
	147	151,2	57	6 x 500	2705/470/1645		54	42	6 562
EHV 63 4P V	216	235,0	62	5 x 630	6448/650/1040		64	54	9 708
	218	265,0	62	5 x 650	6448/650/1040		64	54	10 666
	220	188,0	61	4 x 630	2823/940/2120		54	42	8 221
	222	212,0	61	4 x 630	2823/940/2120		64	54	9 176
	224	282,0	63	6 x 630	4038/940/2120		64	54	11 622
	226	318,0	63	6 x 630	4038/940/2120		64	54	12 678
	228	376,0	64	8 x 630	5253/940/2120		64	54	15 175
	230	424,0	64	8 x 630	5253/940/2120		64	54	16 684
	232	470,0	64	10 x 630	6468/940/2120		64	54	19 159
	234	530,0	64	10 x 630	6468/940/2120		64	54	21 158



URZĄDZENIA DOSTĘPNE W WERSJI PIONOWEJ, POZIOMEJ LUB W UKŁADZIE " V"
 POWYŻEJ PRZEDSTAWIONO WYBRANE MODELE SKRAPLACZY
 KOMPLEKSOWA OFERTA DOSTĘPNA W ODDZIAŁACH FIRMY
 IGLOTECH



Centrala: KWIDZYN Tel./Fax.(055) 279 33 43

Oddziały: TORUŃ Tel./Fax.(056) 622 11 04, GRUDZIĄDZ Tel./Fax. (056) 451 73 00, BYDGOSZCZ Tel./Fax. (052) 348 63 47,
 KATOWICE Tel./Fax. (032) 228 73 00, RASZYN Fax. 022/735 71 30